

THIN FILM CHIP RESISTOR KITS

SURFACE MOUNT CHIP RESISTOR KITS

WATF-1 KITS & WATF-8 KITS (39 OHMIC VALUES)

2	3	4	5	6	7
8	9	10	12	15	18
20	22	27	33	39	42
50	68	72	83	91	100
120	150	180	200	220	270
330	390	420	500	680	720
830	910	1K			

WATF-2 KITS & WATF-7 KITS (65 OHMIC VALUES)

2	5	10	12	15	18
20	22	27	33	39	42
50	68	72	83	91	100
120	150	180	200	220	270
330	390	420	500	680	720
830	910	1K	1.2K	1.5K	1.8K
2K	2.2K	2.7K	3.3K	3.9K	4.2K
5K	6.8K	7.2K	8.3K	9.1K	10K
12K	15K	18K	20K	22K	27K
33K	39K	42K	50K	68K	72K
83K	91K	100K	120K	150K	

WATF-3 KITS & WATF-4 KITS (71 OHMIC VALUES)

SAME VALUES AS WATF-2 KIT WITH THESE ADDITIONAL VALUES

180K	200K	220K	270K	330K	390K
------	------	------	------	------	------

WATF-5 KITS & WATF-6 KITS (74 OHMIC VALUES)

SAME VALUES AS WATF-3 KIT WITH THESE ADDITIONAL VALUES

420K	500K	680K
------	------	------

WATF-9 KITS (78 OHMIC VALUES)

SAME VALUES AS WATF-5 KIT WITH THESE ADDITIONAL VALUES

720K	830K	910K	1M
------	------	------	----

STANDARD TOLERANCE IS 1% FOR ALL KITS.

PART NUMBERING SYSTEM:

KIT PART NUMBER

WATF-X	A	X	KIT	X
SERIES		RESISTIVE		QTY
1, 2		N = Nichrome		A = 10 PCS. EA. VALUE
3, 4		T = Tantalum		B = 25 PCS. EA. VALUE
5, 6		Nitride		C = 50 PCS. EA. VALUE
7, 8				D = 100 PCS. EA. VALUE
9				

EXAMPLE: WATF-4-A-N-KIT-A; CONSISTS OF 10 PCS. EACH VALUE NICHROME RESISTOR FOR WATF-4 STYLE KIT
 WEIGHTED KITS AVAILABLE. PLEASE CONSULT SALES.
 SPECIAL KITS ARE AVAILABLE; MUST HAVE AT LEAST 25 VALUES;
 KITS ARE PACKAGED WITH INDIVIDUAL VALUES IN WAFFLE PACKS.
 WATF KITS HAVE SOLDER TERMINATIONS. PLEASE SPECIFY IF PARTS ARE REQUIRED WITHOUT SOLDER.



MINI-SYSTEMS, INC.
 THIN FILM DIVISION

45 FRANK MOSSBERG DRIVE, ATTLEBORO, MA 02703
 508-226-2111 FAX: 508-226-2211